
S-15 22. 31

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of CALHOUN

Twp 16 S Rge 13 W Sec 15



O = Corner

I, Allison B. Means
RLS 38 certify that on the 16 day of June, 1980, found evidence of the Section corner of SW cor. 15 Township 16 S, Range 13 W of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 16 day of June, 1980.

Description of Original Corner

December, 1844.
G.L.O. Surveyor, J. M. Moore, established Section corner Sec's 15-16-21-22, T. 16 S; R. 13 W; from which:
(1) Pin Oak 15" dia. S23½°E - 31 lks
(2) Pin Oak 14" dia. N8°W - 18 lks
(3) persimmon 8" dia. S23°W - 10 lks
(4) Over cup Oak 10" dia. N73°E-16 lks

Nov. 12, 1954, I witness this corner, 4" pipe, brass cap scribed & T. Beard, 1936, from which: (4) N73°E - 16 lks O.B.T. Over Cup Oak standing. (5) S.G. 14" dia. N62°E-10 lks. (6) Pin O. N65° W-56 lks. (7) Pin O. 8" S55°W-33 lks (8) Pin Oak 7" S 25½°E -61 lks.

Description of Corner Evidence Found

(5) N62°E - 102 lks Sw. Gum stp.
(6) N65°W - 56 lks. Pin Oak standing in good con.
(7) S55°W - 33 lks. stp. hole
(8) S25½°E - 61 lks. nothing
(4) N73°E - 16 lks. stp. hole.

Old Iron Corner by T. Beard, Bradley Lb. Co. Surv. had been knocked out, but I found it after setting aluminum corner lying nearby.

Point of the corner determined by: O.B.T. standing, 3.03 ch. N. O.L.T. & other evidence found.

Description of monument accessories I established to perpetuate the location of this corner.

I set aluminum pipe 30" long, 3½" cap marked as shown below, break-away-base sunk 22" in ground from which:
(6) Pin Oak 14" dia N65°W - 56 lks; Orange band @ 5'; blaze & scribe @ bottom with nail in bl.
(9) White Oak 12" dia. N46¼°E - 109 lks. " " " " " " " " " "
(10) Pin Oak S52½°W-59 lks. " " " " " " " " " "
(11) Pin Oak 12" dia. S41°E-44 lks. Orange band @ 5' blaze & scribe "WT" @ bottom, nail in bl.

NOTE: Witness trees, 6-9-10-11, all have witness tags, painted orange band @ 5 ft; painted blaze @ bottom & scribed "WT" with aluminum nail driven in blaze; DO NOT DISTURB SIGN 6' NE.

CHECKED
Y

Field work executed by: Allison B. Means RLS 38

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the 19 day of June, 1980, in Book 1 Page 31.

Harold L. Watson, Clerk
(Recorder)
by Delois Daniell D.C.

(Show or attach other information on reverse side)

I certify that this instrument was filed for record in the Land Survey Division on the 3rd day of July, 1980, and is truly recorded as Document 2231

Rayford Hudson
(State Surveyor)

Div. Ind 2231 Page 1 of 1. Film Ind.

LSD 76-1 Allison B. Means