
CERTIFIED LAND CORNER RESTORATION – PERPETUATION AND FILING RECORD

Doc. No. 12508
Film
Date
LSD
Office use only

STATE OF ARKANSAS

County of CLARK

Twp 10 South Rge 18 West Sec 33



○ = corner

I, LAMAR KELLEY
RLS 1014 certify that on the 21st day of January, 1997 found evidence of the SE corner of Section 33 Township 10 South, Range 18 West of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 10th day of February, 2000.

Title: SES33T10R18

LSD 76-1

Lamar Kelley

Description of Original Corner

Nov. 22, 1818, a deputy surveyor (name unknown) set a post corner and marked 2 trees:
1) 9" Olive N27W 31 lks.
(NOTE: Olive would be an Ash)
2) 12" Sw. Gum N49E 41 lks.

Description of Corner Evidence Found

Jan. 21, 1997 while performing a survey in Sec. 3–T11S–R18W, we found a 6" x 6" concrete post marked at the intersection of orange lines North and West. *
1) depression – 24" x 6" deep
2) stump hole – 30" x 12" deep

We had been told of this government corner location by an 80–year old man (whose name we did not get) who said his ancestors had worked on the GLO survey crew.

3) 8" Hickory S42E 14.0' – orange/blue band
4) 6" Hornbeam N09E 8.0' – orange/blue band

* Post is turned 45°
* NW face has SE SEC 33 NE face has SW SEC 34
SE face has T11 R18

CHECKED

Point of the corner determined by: existing concrete monument, OBT stump holes

Description of monument accessories I established to perpetuate the location of this corner.

Set 2.5" x 30" aluminum pipe with breakoff, magnetized, polystyrene base with aluminum cap stamped as per diagram right. Monument set over broken glass 27" deep.

Marked 4 trees: with band at 6 feet – base blazed & notched with nail in notch scribed WT
3) 8" Hickory S42E 14.0'
4) 6" Hornbeam N09E 8.0'
5) 14" Water Oak S18W 22.0'
6) 12" Water Oak N56W 22.6'

Location tag on 6 –Bearing tag on 3, 4, 5
Warning sign placed at NW 5'

ARKANSAS GEOLOGICAL COMMISSION
DO NOT DISTURB
T10S – R18W
A | SC
S33 | S34
S4
T11S – R18W
RLS 1014
2-5-2000
LAND SURVEYING DIVISION

Field work executed by: L. Kelley, A. Kelley

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the 23rd day of Feb, 2000 in Book I Page, 205

Pamela D King by Kasey Summerville, D.C.
(Recorder)

(Show or attach other information on reverse side)

I certify that this instrument was filed for record in the Land Survey Division on the 25 day of Feb, 2000, and is truly recorded as Document 12508

(State Surveyor)

Div. Ind. 213 Page 1 of 1 Film Ind.

Filed for Record 23rd day of Feb 2000 at 3:00 O'Clock
PAM D. KING, Circuit Clerk
by Kasey Summerville Deputy Clerk

I 205