
12 Doc. No. 7267
Film
Date 7-10-86
J-9-86 LSD
mi Office use o

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of Clay

Twp 20-N Rge 3-E Sec 12



O = Corner

I, Bernard J. DeClerk
RLS 536 certify that on the 5 th day of May, 1985, found evidence of the southwest corner of section 12 Township 20-N, Range 3-E of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 8 th day of June, 1985.

BERNARD J. DeCLERK
REGISTERED
LAND SURVEYOR
STATE OF
ARKANSAS
NO. 536
SIGNATURE
Bernard J. DeClerk

Description of Original Corner

In 1825, GLO set corner to sections 11-12-13-14 T-20-N R-3-E and marked:

1. 24" B lack oak N.73°E. 17 links.
2. 20" Do S.55°W. 32 links.

Description of Corner Evidence Found

In 1981, I found a 1¼" pipe buried ±8 inches in the center of a lane south, on the outside of a curve in a county road, in line with the center of the county road north and west. I used this corner in a boundary survey and found it to be correct.

Point of the corner determined by: Found pipe in place marking corner, in harmony with other corners in the area and in harmony with location shown on Quadrangle map.

Description of monument accessories I established to perpetuate the location of this corner.

5/30/85, I found same pipe as described above, referenced it, removed it and set in place a standard 2 inch aluminum pipe A. G. C. monument. Monument is 30 inches long with a plastic breakoff footplate and 3 inch cast aluminum cap, marked as shown at right. Buried Monument ±6 inches over broken glass and set a steel fence post with monument sign above location poster attached, 17.7 feet east and referenced:

3. 36" white oak N.5°W. 103.0 feet. 4. 12" Elm S.75°W. 69.3 feet. 5. Power pole N.68°-30"E. 37.9 feet.

Trees 3. and 4. marked with notch at base with concrete nail driven in notch, blazed ±16 inches above ground with figures WT scribed in blaze, banded ±4 inches wide, ±5 feet above ground and bark blazed above band with bearing tree sign nailed over bark blaze. All tree marks painted orange.

ARKANSAS GEOLOGICAL COMMISSION · DO NOT DISTURB · LAND SURVEY DIVISION
T20N R3E
11 12
14 13
TYPE C
RLS 536
1985

Field work executed by: Bernard J. DeClerk, RLS 536 and Bernard J. DeClerk, Jr.

CHECKED
7-11-85

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the 18th day of June, 1985, in Book 9 Page 655
Gary Maze, Clerk
Bufette Berry Dc.
(Recorder)

I certify that this instrument was filed for record in the Land Survey Division on the 10th day of July, 1985, and is truly recorded as Document 7267
(State Surveyor)

(Show or attach other information on reverse side)

Div. Ind. J-21 Page 1 of 1. Film Ind.

LSD 76-1
B28P73