
A-9

STATE OF ARKANSAS
County of CLEBURNE

Twp 11 N Rge 11 W Sec 33



I, Charles F. Reding
RLS 975 certify that on the 12 th day of November, 1999, found evidence of the NW corner of Sec. 4 Township 11 N, Range 11 W of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 13th day of December, 1999.

REGISTERED PROFESSIONAL LAND SURVEYOR
STATE OF ARKANSAS
NO. 975
SIGNATURE
CHARLES F. REDING

LSD 76-1

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

Doc. No. 12474
Film
Date
LSD
Office use only

Description of Original Corner

In January, 1833, Mr. C.H. Pelham, Deputy Surveyor, intersected the south boundary of T12N, R11W, 73 links (48.2 ft.) West of the corner of Sections 32 & 33 where he set a post for the corner of Sections 4 & 5, T11N, R11W, and marked the following trees:
1. 15" White Oak S29°W 76 lks(50.2 ft.)
2. 12" White Oak S11°E 21 lks(13.9 ft.)

Description of Corner Evidence Found

There was no existing monument or other evidence at this corner location. A stone monument and evidence of the original G.L.O. trees was found at the corner of Sections 32 & 33, T12N, R11W, 48.2 ft. East of this point.

DEC 20 1999

99 DEC 13 PM 2:01

Point of the corner determined by: Rfefernce to the corner of Sections 32 & 33, T12N, R11W.

Description of monument accessories I established to perpetuate the location of this corner.

I set a Berstsen A2BR monument furnished by the Arkansas Geological Commission. This monument was set 24" deep over broken glass . The existing stone and iron rod were reset next to the new monument and it was surrounded with a collar of stones. The following trees were marked with an orange painted band about eye level and an orange painted blaze at the base. A "P.K." nail pointing to the corner was driven in a notch below the blaze and an aluminum bearing tree tag was placed above the band.

3. 8" Hickory S83°E 25.3 ft.
4. 6" Hickory S08°E 47.1 ft
5. 16" Post Oak S33°W 50.9 ft
6. 8" Pine S78°W 74.3 ft.

CHECKED

T12N R11W
S 32
S 5 | S 4
T11N R11W
RLS 975
1999

Field work executed by: Charles Reding and Grant Price

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the _____ day of _____, 19__, in Book L Page 213.

(Recorder)

I certify that this instrument was filed for record in the Land Survey Division on the 20 day of December 1999, and is truly recorded as Document 12474.

(State Surveyor)

(Show or attach other information on reverse side)

Div. Ind. A-9 Page 1 of 1. Film Ind.