
Doc. 10209

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of ~~St Francis~~ Cross

Twp 9N Rge 4E Sec 32



O = Corner

I, DAVID P. REINOLD
RLS 0839 certify that on the 14th day of August, 1990, found evidence of the NW corner of S. 32 Township 9N, Range 4 E of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 15th day of AUGUST, 1990.

REGISTERED PROFESSIONAL LAND SURVEYOR
STATE OF ARKANSAS
NO. 839
SIGNATURE
DAVID P. REINOLD
AND SURVEYOR

Description of Original Corner

Reference page 539 for T9N, R4E of the typed-copy of the USGLO field notes-original survey subdivision of T9N, R4E, obtained from the office of State Surveyor for Arkansas,(sub-page 19). On Feb. 23, 1846 the D.S. for the USGLO set a post for the corner to sections 29-30-31-32 from which:

(1) 10" White oak brs. N75°E 8 links
(2) 12" Post oak brs. S49½°E 53 links
(3) 14" White oak brs. S44°W 49½ links
(4) 12" Pine brs. N22¼°W 44 links

From this corner the USGLO surveyor ran line west btwn S. 30 & 31 and called a 20 lk wide creek call at 5 chains.

From this corner the USGLO surveyor also ran line north 11.75 chains & struck a blackgum and creek at 17.0 chains.

Description of Corner Evidence Found

Search coordinates were developed from ties to proven GLO corner locations 1 mile south and ½ mile north. The following evidence was found from a diligent search within a few feet of the developed search point:

(1) N75°E 5.3 ft, stumphole with whiteoak sprout from collar
(2) S49½°E 35 ft., stumphole, hardwood, species not determined from digging.
(3) S44°W 32.7 ft., definate large hardwood stumphole
(4) N22¼°W 29 ft., deep-tap-root stumphole, pine

Measured 330 ft. west to confirmed creek call. Measured North 778 ft. to large stumphole on line, and 1125 feet north to a point in a creek which runs NE-SW as called for in the original field notes.

Point of the corner determined by: ALL four OBT stumpholes, creek calls north & west, and stumphole for line tree which all match well with proration for corner using proven GLO corners to N & S.

Description of monument accessories I established to perpetuate the location of this corner.

I SET AN ARKANSAS GEOLOGICAL COMMISSION ALUMINUM-CAP MONUMENT WITH BREAK-OFF PLASTIC BASE OVER GLASS APPROXIMATELY 12" IN GROUND WITH THE CAP STAMPED AS SHOWN AT RIGHT. THE FOLLOWING NEW BEARING TREES WERE BANDED AT 6' WITH A RED BAND, BASE-BLAZED AND SCRIBED "WT" FACING THE MONUMENT LOCATION. BEARING TREE TAGS & LOCATION TAGS WERE PLACED ON THE TREES. AN ALUMINUM NAIL WAS DRIVEN IN THE SIDE OF THE TREE AT THE EXACT POINT FROM WHICH THE DISTANCE MEASUREMENTS WERE TAKEN. AN ALUMINUM POST WITH MONUMENT SIGN WAS DRIVEN 1.1 FEET SOUTHEAST OF THE MONUMENT.:

(1) 12" White Oak N03°E 6.4 ft.
(2) 7" White Oak N68°E 11.3 ft.
(3) 8" Red Oak S15°E 18.8 ft.
(4) 14" Red Oak S37°W 24.5 ft.

ARKANSAS GEOLOGICAL COMMISSION
DO NOT DISTURB
T9N
30 | 29
31 | 32
R4E
1990 RLS 0839
LAND SURVEY DIVISION

FILED FOR RECORD
AUG 27 1990 at 1:42 P M
Recorded in book Plat 3 Page 135
Vernon D. Horton
CIRCUIT CLERK AND EX-OFFICIO RECORDER
CROSS COUNTY, ARKANSAS
By: Treva McClintock, DC

Field work executed by: David P. Reinold, Keith Murders

CHECKED
8
10-5-90

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the _____ day of _____, 19__, in Book _____ Page _____.

_____
(Recorder)

I certify that this instrument was filed for record in the Land Survey Division on the 04 day of October, 1990, and is truly recorded as Document 10209

Everett Rowland
(State Surveyor)

LSD 76-1

(Show or attach other information on reverse side)

Div. Ind. V-5 Page 1 of 1. Film Ind. _____