
81-27200

2853 5.36

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of Pulaski

Twp 4 N Rge 12 W Sec 36



O = Corner

I, William F. Davis, Jr.
RLS 198 certify that on the 7 day of July, 1981, found evidence of the E 1/4 corner of Sec. 36 Township 4 N, Range 12 W of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 7 day of July, 1981.

WILLIAM F. DAVIS, JR.
REGISTERED
LAND SURVEYOR
STATE OF
ARKANSAS
NO. 198
SIGNATURE

William F. Davis

LSD 76-1

Description of Original Corner

(From GLO notes)
"....Set 1/4 Sec post from which a B Jack 6" in dia bears N82W 14 L & a do 8 in dia bears S82E 18 L...".

Description of Corner Evidence Found


Iron pipe in pile of stones.

(1) N82W 14 L, timber cleared, second growth. No sign of original BT.

(2) S82E 18 L, (Same as above).

Point of the corner determined by: Recovered Iron pipe in pile of stones in line with abandoned road to South. Survey by myself to West and South proved the point was established as the subject corner.

At the corner point I set a monument consisting of a 2" dia. alumn. pole 30" in length with a cast alumn. breakoff base and 3 1/4" inside fit alumn. cap marked as shown at right. Permanent magnets are built into cap & breakoff portion. Monument is set 26" deep over broken glass. From the monument a (3) 9" Black Oak with nail at base painted red with "BT" sign 4' high bears West @ 16.1'; (4) 5" Black Oak with alumn. nail at base painted red with "BT" sigh 4' high bears S80E @ 16.7'; (5) 8" Black Oak with alumn. nail at base painted red with "BT" sign 4' high bears S10W @ 34.5'.



CHECKED

Field work executed by: John Steve Robinson Jamie Robinson

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the 14th day of July, 1981, in Book 81 Page 27200

(Recorder)

I certify that this instrument was filed for record in the Land Survey Division on the 23rd day of July, 1981, and is truly recorded as Document 2853.

J. L. Young
(State Surveyor)

(Show or attach other information on reverse side)


Div. Ind. 2853 Page 1 1. Film Ind.

81-27210

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of Pulaski

Twp 4 N Rge 12 W Sec 36



O = Corner

I, William F. Davis, Jr.
RLS 198 certify that on the 7 day of July, 1981, found evidence of the E 1/4 corner of Sec. 36 Township 4 N, Range 12 W of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 7 day of ~~July~~, 19~~81~~.

WILLIAM F. DAVIS, JR.
REGISTERED
LAND SURVEYOR
STATE OF
ARKANSAS
NO. 198
SIGNATURE

Description of Original Corner

(From GLO notes)
"....Set 1/4 Sec post from which a B Jack 6"in dia bears N82W 14 L & a do 8 in dia bears S82E 18 L...".

Description of Corner Evidence Found

FILED FOR RECORD
JUL 14 10 38 AM '81
BY
JAMES [illegible] ALEXANDER
PULASKI CO. CIRCUIT CLERK


Iron pipe in pile of stones.

(1) N82W 14 L, timber cleared, second growth. No sign of original BT.

(2) S82E 18 L, (Same as above).

Point of the corner determined by: Recovered Iron pipe in pile of stones in line with abandoned road to South. Survey by myself to West and South proved the point was established as the subject corner.
Description of monument accessories I established to perpetuate the location of this corner.

At the corner point I set a monument consisting of a 2" dia. alumn. pole 30" in length with a cast alumn. breakoff base and 3 1/4" inside fit alumn. cap marked as shown at right. Permanent magnets are built into cap & breakoff portion. Monument is set 26" deep over broken glass. From the monument a (3) 9" Black Oak with nail at base painted red with "BT" sign 4' high bears West @ 16.1'; (4) 5" Black Oak with alumn. nail at base painted red with "BT" sign 4' high bears S80E @ 16.7'; (5) 8" Black Oak with alumn. nail at base painted red with "BT" sign 4' high bears S10W @ 34.5'.



Field work executed by: John Steve Robinson Jamie Robinson

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the _____ day of _____, 19 __, in Book Page _____.

(Recorder)

I certify that this instrument was filed for record in the Land Survey Division on the ___ day of _____, 19___, and is truly recorded as Document _____.

(State Surveyor)

LSD 76-1

(Show or attach other information on reverse side) Div. Ind.____Page____. Film Ind._____

Duplicate