
3272
S.23

CERTIFIED LAND CORNER RESTORATION - PERPETUATION AND FILING RECORD

STATE OF ARKANSAS
County of Scott

Twp 1 N Rge 29 W Sec (23)-24-25-26



O = Corner SE-23

I, Roy W. Hudgens
RLS 371 certify that on the 23 day of January, 19 79, found evidence of the Section corner of Sec. (23)-24-25-26 Township 1 N, Range 29 W of the Fifth Principal Meridian, and that I have established a new monument and accessories as described hereon to perpetuate the location of this corner and that the found evidence and restored monument and accessories are correctly shown.

IN WITNESS WHEREOF, I have hereunto set my hand and stamp this 21 day of MAY, 1980.

Evans
Woodral
Nelson

ROY W. HUDGENS
REGISTERED
LAND SURVEYOR
STATE OF
ARKANSAS
NO. 371
Roy W. Hudgens
SIGNATURE

LSD 76-1

Description of Original Corner

Section corner post set for Sections 23-24-25-26, T1N, R29W by Deputy Surveyor in 1843. No record of bearing trees.

Description of Corner Evidence Found

T1N	R29W
S23	S24
S26	S25

1934 F.12/3/81

6" concrete post with 3½" diam brass cap mkd in mound of stone. Set by dependent resurvey by proportionate distance from which (5) 12" post oak bears N14½°E32 Lks.
(6) 8" pine bears S25 3/4°E61 Lks.
(7)10" post oak bears S26¼°W49 Lks.
(8) 5" pine bears N54 3/4°W56 Lks.
1979 found the following bearing trees
(5)14" post oak bears N14½°E32 Lks.
(6)14" pine bears S25 3/4°E61 Lks.
(7) No evidence
(8)13" pine bears N54 3/4°W61½ Lks has base blaze.

Point of the corner determined by: Single proportionate distance. ~~Double proportionate distance.~~

Description of monument accessories I established to perpetuate the location of this corner.

~~Set aluminum pipe 30" long, 1 3/4" diam....ins. in ground over broken glass in mound of stone painted red with 3" aluminum cap marked as shown at right.~~

Set aluminum ~~pipe~~ 1...ins. E...of corner with 5/8 bar cap.

T1N	R29W
S23	S24
S26	S25

1934

Monument in good condition.

(9) 13" pine bears N54 3/4°W61½ Lks.
(10) 16" post oak bears N14½°E32 Lks.
(11) 14" pine bears S25 3/4°E61 Lks.
(12) 14" white oak bears S32½°W36½ Lks.

All BT's are base blazed, scribed "BT". ...m. nail in base' red band 6' high ... 3 BT tag 54-6 location tag on ...ee No 9-10-11-12

Field work executed by: Roy W. Hudgens U.S.F.S. 2/2/79

OFFICE OF CLERK AND RECORDER: (Show filing data)
This document was filed for record on the 12 day of June, 1980, in Book 2 Page 96.

Estelyn Simmons
(Recorder) by: Martha E. Hankins

I certify that this instrument was filed for record in the Land Survey Division on the 16th day of Oct, 1981, and is truly recorded as Document 3272.

J. L. Lyon
Acting (State Surveyor)

(Show or attach other information on reverse side) Div. Ind R-21 Page 1 of 1. Film Ind.

96